

## Technical data sheet

### Accessories - Tapes

Refª.	Measurements	Box /	Ø (±5%)
<b>FT01</b>	50mm x 45m	36 Rls	± 12,1cm
<b>FT02</b>	75mm x 50m	24 Rls	± 12,1cm
<b>FT06</b>	50mm x 10m	96 Rls	± 9,4m

### Technical Data

Thickness (ISO 534)	30 +/- 6% µm
Weight (silicone paper) (ISO 536)	65 g/m <sup>2</sup>
Total Thickness (ISO 534)	64 µm
Adhesion Force (FTM 9)	9 mm/min
Tear (FTM 8)	200 h
Steam Transmission (DIN 53122)	-0,1 perm
Tension Resistance (DIN 53122)	+40 N/15mm
Usage Temperature	-20°C to 80°C

### Composition

Aluminum foil laminated with Acrylic Adhesive with Silicone Paper protection.

### Application Areas

- Insulation Joints
- HVAC ducts
- Chimney flues
- Flexible exhaust pipe / water heaters
- Automotive pipe gaskets
- Etc.



#### Note:

The Tape should be stored in a dry and clean place, at a temperature of approximately 23°C and a Relative Humidity of 50%.

SPACE REFLEX® recommends special attention so that the contact surfaces are clean, free from dust, oils, or any other non-stick substance.

The technical data contained in this document are for guidance only for the End User, not implying any legal guarantee to certain properties, since there are numerous influences that may occur during the handling and use of the product.